

# EMC SYMMETRIX VMAX 20K



VMAX 20K high-density configurations support up to 3,200 drives, consuming 33 percent less space, 35 percent less weight, and 27 percent less power compared with 3.5-inch drives.

The EMC® Virtual Matrix Architecture™ is a new way to build storage systems that transcends the physical constraints of all existing architectures by scaling system resources through common building blocks called EMC® Symmetrix® VMAX® 20K engines.

A single VMAX 20K engine provides the complete foundation for a high-availability Symmetrix VMAX 20K system. Each VMAX 20K engine contains two Symmetrix VMAX 20K directors and redundant interfaces to the EMC Virtual Matrix™ interconnect. Each Symmetrix VMAX 20K director consolidates front-end, global memory, and back-end functions, enabling direct memory access to data for optimized I/O operations.

VMAX 20K engines are interconnected via a set of multiple active fabrics that provides scalable performance and high availability. VMAX 20K engines can be added non-disruptively to provide linear scale-out of Symmetrix system resources. The Virtual Matrix is architected to scale to dozens of engines, geographically dispersed throughout a data center, delivering unprecedented scale of infrastructure services under a single point of management.

---

## VMAX 20K ENGINE MAXIMUM SPECIFICATIONS

- Four Quad-core 2.33 GHz Intel® Xeon® processors
- Up to 128 GB of memory
- Virtual Matrix bandwidth: 24 GB/s

---

## VMAX 20K MAXIMUM SYSTEM SPECIFICATIONS

- Eight VMAX 20K engines
- 1 TB of memory
- Virtual Matrix bandwidth: 192 GB/s

---

## VMAX 20K INTERCONNECT

Industry-standard RapidIO® fabric (Virtual Matrix Architecture is extensible to other standard interconnects.)

---

## CONNECTIVITY

Symmetrix VMAX 20K systems are available in configurations supporting up to eight VMAX 20K engines with a maximum of 128 front-end ports. Optimized hardware logic and data protection encoding ensures end-to-end data integrity with automated channel failover for a maximum availability and load balancing. Symmetrix VMAX 20K systems support all popular hardware and operating system platforms, storage area networks (SANs), and high-availability cluster environments. IPv6, IPsec, and compression support are available with 1 Gb/s Ethernet ports. IPv6 support is available with 10 Gb/s Ethernet.

---

## PROTOCOL

8 Gb/s Fibre Channel Host/ SAN Ports	4-128 per array, 4-16 ports per engine
8 Gb/s Fibre Channel Remote Replication Ports	2-32 per array, 2-4 ports per engine
8 Gb/s FICON Host Ports	4-64 per array, 4-8 ports per engine
4 Gb/s Fibre Channel Host/SAN Ports	4-128 per array, 4-16 ports per engine
4 Gb/s Fibre Channel Remote Replication Ports	2-32 per array, 2-4 ports per engine
4 Gb/s FICON Host Ports	4-64 per array, 4-8 ports per VMAX engine
10 GB/s 1 Gb/s Ethernet Remote Replication Ports	2-32 ports per array, 2-4 ports per engine
10 GB/s FCoE Host Parts	4-64 per array, 4-8 ports per engine
10 GB/s iSCSI Host Parts	4-64 ports per array, 4-8 ports engine
1 GB/s GigE Remote Replication Ports	2-32 ports per array, 2-4 ports per engine
1 Gb/s iSCSI Ports	4-64 per array, 4-8 ports per engine

## USABLE SYSTEM PORTS

Mixed combinations of the above port types depend upon the configuration. Refer to the EMC Support Matrix at, or contact your local EMC sales representative for specific configuration support. EMC Symmetrix VMAX 20K systems are available in two to 11-bay configurations for up to two petabytes of usable storage capacity in a single system.

---

## DISK DRIVE AND ENTERPRISE FLASH DRIVE CONNECTIVITY

The Symmetrix VMAX 20K drive infrastructure is architected with 4 Gb/s dual-ported Fibre Channel drives, Enterprise Flash drives, SAS drives, and SATA drives, each supported by two independent I/O channels with automatic failover and fault isolation.

---

### 3.5" DISK DRIVES

CAPACITY	146 GB	300 GB	300 GB	450 GB	450 GB
Rotational Speed (rpm)	15,000	10,000	15,000	10,000	15,000
Form Factor	3.5 in	3.5 in	3.5 in	3.5 in	3.5 in
Internal Data Rate (Mb/s)	685-1,142	1,010-1,840	685-1,142	1,010-1,840	1,051-2,225
Average Seek Time (read/write)	3.4/3.9 ms	3.8/4.4 ms	3.4/3.9 ms	3.8/4.4 ms	3.4/3.9 ms
Raw Capacity	145.7 GB	292.7 GB	292.6 GB	439.0 GB	439.0 GB
<b>FORMATTED CAPACITY</b>					
Open Systems	143.5 GB	288.1 GB	288.1 GB	432.2 GB	432.2 GB
Mainframe	139.3 GB	279.7 GB	279.7 GB	419.6 GB	419.6 GB
IBM i	141.7 GB	288.2 GB	288.2 GB	435.1 GB	435.1 GB

---

### 3.5" DISK DRIVES (CONTINUED)

<b>CAPACITY</b>	<b>600 GB</b>	<b>600 GB</b>	<b>900 GB</b>	<b>1 TB</b>	<b>2 TB</b>	<b>3 TB</b>
Rotational Speed (rpm)	10,000	15,000	10,000	7,200	7,200	7,200
Form Factor	3.5 in	3.5 in	3.5 in	3.5 in	3.5 in	3.5 in
Internal Data Rate (Mb/s)	1,010-1,840	1,051-2,225	1319-2232	470-1,070	470-1,070	470-1,070
Average Seek Time (read/write)	3.8/4.4 ms	3.4/3.9 ms	3.8/4.3 ms	8.2/9.2 ms	8.2/9.2 ms	8.2/9.2 ms
Raw Capacity	585.4 GB	585.4 GB	894.9 GB	1000.2 GB	1912.1 GB	3000.5 GB
<b>FORMATTED CAPACITY</b>						
Open Systems	576.3 GB	576.3 GB	881.1 GB	984.8 GB	1882.7 GB	2954.4 GB
Mainframe	559.5 GB	559.5 GB	855.3 GB	956.0 GB	1827.6 GB	2868.0 GB
IBM i	580.1 GB	580.1 GB	870.2 GB	n/a	1912.1 GB	2955.1 GB

---

### 2.5" DISK DRIVES

<b>CAPACITY</b>	<b>146/300 GB</b>	<b>300 GB</b>	<b>450 GB</b>	<b>600 GB</b>	<b>900 GB</b>	<b>1 TB</b>
Rotational Speed (rpm)	15,000	10,000	10,000	10,000	10,000	7,200
Form Factor	2.5 in	2.5 in	2.5 in	2.5 in	2.5 in	2.5 in
Internal Data Rate (Mb/s)	1554-2267	1219-2232	1219-2232	1219-2232	1219-2232	673/1304
Average Seek Time (read/write)	2.8/3.3 ms	3.7/4.2 ms	3.7/4.2 ms	3.7/4.2 ms	3.7/4.2 ms	7.7/8.7 ms
Raw Capacity	145.7/292.6 GB	292.7 GB	439.0 GB	585.4 GB	585.4 GB	1000.2 GB
<b>FORMATTED CAPACITY</b>						
Open Systems	143.5/288.1 GB	288.1 GB	432.2 GB	576.3 GB	881.1 GB	984.8 GB
Mainframe	139.3/279.7 GB	279.7 GB	419.6 GB	559.5 GB	855.3 GB	956.0 GB
IBM i	141.7/288.2 GB	288.2 GB	435.1 GB	580.1 GB	870.2 GB	985.0 GB

---

### ENTERPRISE FLASH DRIVES

<b>CAPACITY</b>	<b>100 GB</b>	<b>200 GB</b>	<b>400 GB</b>
Form Factor	2.5 in & 3.5 in	2.5 in & 3.5 in	2.5 in & 3.5 in
Internal Data Rate (Mb/s)	800-1,600	800-1,600	800-1,600
Raw Capacity	100.0 GB	200.0 GB	400.0 GB
<b>FORMATTED CAPACITY</b>			
Open Systems	98.4 GB	196.9 GB	393.8 GB
Mainframe	95.6 GB	191.2 GB	382.3 GB
IBM i	98.5 GB	197.0 GB	389.8 GB

## SYSTEM CAPACITY IN TERABYTES (NON-FLASH)

# OF DRIVES		146 GB DRIVES (3.5")		3 TB DRIVES (3.5")	
		Min.	Max.	Min.	Max.
<b>MIRRORED</b>		48	3,200	48	2,400
	Open Systems	2.8	225.0	37.6	2,067
	Mainframe	2.7	218.4	36.5	2,006
<b>RAID-5 3+1</b>					
	Open Systems	4.3	337.5	56.4	2,067
	Mainframe	4.1	327.7	54.8	2,006
<b>RAID-5 7+1</b>					
	Open Systems	5.0	393.8	65.9	2,055
	Mainframe	4.8	382.3	63.9	1,995
<b>RAID-6 6+2</b>					
	Open System	4.3	337.5	56.4	2,067
	Mainframe	4.1	327.7	54.8	2,006
<b>RAID-6 14+2</b>					
	Open System	5.0	393.8	79.0	2,055
	Mainframe	4.8	382.3	76.7	1,955

Configurations with mixed drive capacities and speeds are allowed depending upon the configuration. 64 GB of total capacity will be reserved for internal Symmetrix file system use. All capacities are based on 1 GB = 1,000,000,000 bytes. Actual usable capacity may vary depending upon configuration.

## SYMMETRIX DATA AT REST ENCRYPTION

Symmetrix Data at Rest Encryption (D@RE) is delivered through a unique Symmetrix VMAX 20K engine model with built-in, hardware-based data encryption. Data is encrypted when written to drives and decrypted when read from drives with no impact on performance or local and remote replication. D@RE addresses security and compliance concerns regarding data exposure when drives are removed or arrays are replaced.

## PHYSICAL AND COOLING SPECIFICATIONS

	HEIGHT*	WIDTH	DEPTH	AREA	WEIGHT	POWER	COOLING
	(IN/CM)	(IN/CM)	(IN/CM)	(IN/CM)	(LB/KG)	(KVA)	(BTU/HR)
System bay (four engine)	76.66/194.7	30.2/76.7	41.88/106.4	42.0/106.7	1,830/830.0	4.1	13,700
System bay (eight engine)	76.6/194.7	30.2/76.7	41.88/106.4	42.0/106.7	2,774/1,258.3	7.8	26,300
Standard storage bay	76.6/194.7	30.2/76.7	41.88/106.4	42.0/106.7	2,278/1,033.3	6.1	19,800
High density storage bay	75.0/190.5	24.02/61.0	41.88/160.4	42.0/160.7	1674/759.3	4.9	15,200

All dimensions are cabinet/enclosure size without shipping brackets or securing brackets. Weight, power, and cooling are the maximum for a full configuration. Cooling is front to rear for system bay and front to top for storage bays. \*An additional 18 in. (45.7 cm) is recommended for ceiling/top clearance.

## POWER SPECIFICATIONS (STORAGE BAY AND SYSTEM BAY)

	N. AMERICA 3-PHASE (DELTA 4- WIRE) (3L+1G)	INTERNAT. 3-PHASE (WYE 5- WIRE) (3L+1N+1G)	N. AMERICA SINGLE-PHASE 3-WIRE (2L+1G)	INTERNAT. SINGLE-PHASE 3-WIRE (1L,1N,1G)
<b>INPUT VOLTAGE (VAC)</b>	200-240	200-240	200-240	200-240
<b>FREQUENCY (HZ)</b>	50-60	50-60	50-60	50-60
<b>CIRCUIT BREAKER (AMPS), RECOMMENDED</b>	50	32	30	32
<b>AC POWER CONNECTIONS</b>	2 per bay	2 per bay	4 per bay	4 per bay
<b>POWER CONNECTOR</b>	CS-8365C	S52.30	L6-30P	L6-30P
<b>USER CONNECTOR</b>	See Note 1	See Note 1	See Note 1	See Note 1

Specifications given are for the power connectors located inside the Symmetrix VMAX 20K system and storage bays. EMC offers a selection of power cable extensions with different power connectors for connection to the customer's power source. The power cable extension type desired must be verified at the time of quotation and ordering.

\* L = line or phase, N= neutral, G= ground

Note 1: Refer to EMC® Symmetrix® VMAX® Family Physical Planning Guide for details.

## ENVIRONMENTAL SPECIFICATIONS (OPERATING)

Temperature (F/C)	50-90/10-32
Altitude (ft/m), max.	7,500/2,286
Humidity (%), Non-condensing	20 - 80
Raised Floor	Recommended

## CONTACT US

To learn more about how EMC products, services, and solutions can help solve your business and IT challenges, contact your local representative or authorized reseller—or visit us at [www.EMC.com](http://www.EMC.com).

## RADIO FREQUENCY INTERFERENCE (RFI)

Electro-magnetic fields which include radio frequencies can interfere with the operation of electronic equipment. EMC Corporation products have been certified to withstand radio frequency interference in accordance with standard EN61000-4-3. In Data Centers that employ intentional radiators, such as cell phone repeaters, the maximum ambient RF field strength should not exceed 3 Volts /meter.

REPEATER POWER LEVEL (WATTS)	RECOMMENDED MINIMUM DISTANCE (FEET/METERS)
1	9.84 ft (3m)
2	13.12 ft (4 m)
5	19.69 ft (6m)
7	22.97 ft (7m)
10	26.25 ft (8m)
12	29.53 ft (9m)
15	32.81 ft (10m)

EMC2, EMC, Symmetrix, Virtual Matrix, Virtual Matrix Architecture, VMAX, and the EMC logo are registered trademarks or trademarks of EMC Corporation in the United States and other countries. Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U. S. and other countries. All other trademarks used herein are the property of their respective owners. © Copyright 2013 EMC Corporation. All rights reserved. Published in the USA. 5/13 Specification Sheet H6176.32